

Supermicro CSE-836BE2C-R1K03B

3U chassis - supports for maximum motherboard sizes: 13.68" x 13" E-ATX and ATX 16 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay 16-port 3U SAS3 12Gbps dual-expander backplane, support up to 16x 3.5-inch SAS3/SATA3 HDD/SSD 1U 800/1000W Redundant Titanium Single Output Power Supply W/PMBus 7 Full-height & full-length expansion slot(s) 3 x 8cm hot-swap redundant PWM cooling fans(s) 2 x 8cm hot-swap exhaust fan(s) & air shrou

Product code	202-12337
Part number	CSE-836BE2C-R1K03B
EAN	672042176045
Manufacturer	**Supermicro**
Availability	Not in stock
Warranty	**24** months
Hmonitor	**29** $/€
The price includes all legal fees	

Set a watchdog Add to compare list

Parameters

MB Format	"13.68"x13""
Backplane expander	ano
W Chassis format	0
Depth (mm)	647
Internal LP	0
2.5" Drive bays	0
SAS3 SATA 12 Gbs	8
Optional additional SAS SATA slots	0
3.5" Drive bays	16
Optional additional SAS3 SATA slots	0
HDD disks	
NVMe slots	
Optional additional NVMe SAS3 slots	0
NVMe SAS3 slots	0
Number of power supplies	2
SAS SATA 6Gbs slots	0
Slot FH	0
Slot FH LL	0
Slot FH HL	0
Slot FH L length	
Slot LP	7
Certification	Titanium
Size in U	3
Power (W)	1000

Price development

Your browser does not support charts :-

Stock allocation and delivery options

- Personal pick up - Prague
- Personal pick up - kozrov pod kadaňským
- **Internal LAN - 97.142.xxx.xxx/16**
- **minutes** and **up** - **minut** pou**ž**ívání**m**
- Courier Prague
- **Internal** use only - **Interní** použití
- Transport company in Cz
- Transport company across Europe
- **minutes** in **to** use **t**ransport **t**ime

Motherboard for CSE-836BE2C-R1K03B

X10DRH-i	X10DRH-iT
X10DRH-CT	X10DRH-C
X10DRH-iLN	X10DRH-CLN4

System Cooling

Fans	3 x 8cm hot-swap redundant PWM cooling fan(s) & air shroud

System Monitoring

Chassis intrusion switch

Operating temperature (System)

Operating Temperature Range	5°C - 35°C (41°F - 95°F)
Non-Operating Temperature Range	-40°C - 70°C (-40°F - 158°F)
Operating Relative Humidity Range	8% - 90% (non-condensing)
Non-Operating Relative Humidity Range	5% - 95% (non-condensing)

Power Supply

1U 800/1000W Redundant Titanium Single Output Power Supply W/PMbus	
Power Efficiency	96%
Total Output Power and Input	800W with Input 100 - 127Vac 1000W with Input 200 - 240Vac
AC Input Frequency	50-60Hz
Dimensions (L x W x H)	336 x 76 x 40 mm

Regulatory (Power Supply)

Power Supply Safety / EMC	BSMI CB/EMC CCC FCC Class A UL/CB UL/CUL

Fans

Chassis	3 x 8cm hot-swap redundant PWM cooling fan(s) & air shroud

Power Supply

Power Distributor	PDB-PT836-8624 O/P- 12V/135A +5V Max: 40A +5V Max: 2.5A -12V Max: 0.5A
+5Vsb	Max: 4A / Min: 0A

Backplane

Total Output Power and Input	800W with Input 100 - 127Vac 1000W with Input 200 - 240Vac
AC Input Frequency	50-60Hz
Dimensions (L x W x H)	336 x 76 x 40 mm
Chipset Type	Backplanes (gold finger)
+12V	Max: 66.7A (1050Vac - 127Vac) Max: 83A (200 - 240)
Certification	Titanium

Form Factor

CSE-836BE2C-R1K03B	SuperChassis 836BE2C-R1K03B

Processor Support

- Dual and Single Intel® and AMD processors

Dimensions

Height	5.2" (132 mm)
Width	17.2" (437 mm)
Depth	25.5" (647 mm)
Gross Weight	72 lbs (32.66 kg)
Packaging (W x H x L)	26.6" (676 mm) x 13" (330 mm) x 39.9" (1013 mm)
Available Color	Black

Expansion Slots

- 7 Full-height & full-length expansion slot(s)

Drive Bays

16 x 3.5" Hot-swap drive bay	
Optional 2 x 2.5" hot-swap drive bay	

Rack Mount

Mounting Rails(s)	MCP-410-00007- 1 Rail set, quick-quick, default for 2.5U 12.7"W
Mounting Rails(s)	MCP-290-00052- 1 Rail set, quick-release for 2.5U 12.7"W

Accessory

Power Supply & Accessory	PWS-1K02A-1R	2 1U 1000W Redundant Power Supply Titanium W/PMbus 76X65X4mm,ROHS/EACH
Power Distributor	MCP-220-00075-	16 Black 4pin 5.5 hot-swap 3.5"- HDD tray
Drive Tray(s)	MCP-220-00007-	1 Black USB/COM port tray for SC825, 836
Drive Tray(s)	MCP-220-00007-	1 Black DVD dummy cover for SC825, 836
Fan(s)	FAN-0125A-4	3 80X80X38 mm 7K RPM Chassis Middle Fan w/ Housing
Fan(s)	FAN-0125A	2 80X32 mm 6.7K RPM SC836 Rear Exhaust Fan w/ Housing
Cable(s)	CBL-FRONT-CNTL-16-TO-16 PIN,RA,RND-TUBE,75CM,28AWG	1
Cable(s)	CBL-0071L-	1 CBL,FRONT-CNTL,16 PIN,RA,RND TUBE,75CM,28AWG

HDD Backplane

HDD Backplane	BPN-SAS3- 836E1-2	1 16-port 3U SAS3 12Gbps dual-expander backplane, support up to 16x 3.5-inch SAS3/SATA3 HDD/SSD

Air Shroud

Air Shroud	MCP-310-39001- 0N	1 SCS35/836/936 Intel DP X9-X10 PC air shroud 136mmX13mmX13mm

Standard Parts List

Part Number	Qty	Description
MCP-310-39001-0N	1	SCS35/836/936 Intel DP X9-X10 PC air shroud 136mmX13mmX13mm
BPN-SAS3-836E1-2	1	16-port 3U SAS3 12Gbps dual-expander backplane, support up to 16x 3.5-inch SAS3/SATA3 HDD/SSD
CBL-0071L-	1	CBL,FRONT-CNTL,16 PIN,RA,RND TUBE,75CM,28AWG



Detailed information

Key Features

1. 3U chassis - supports for maximum motherboard sizes: 13.68" x 13" E-ATX and ATX
2. 16 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
3. 16-port 3U SAS3 12Gbps dual-expander backplane, support up to 16x 3.5-inch SAS3/SATA3 HDD/SSD
4. 1U 800/1000W Redundant Titanium Single Output Power Supply W/PMbus
5. 7 Full-height & full-length expansion slot(s)
6. 3 x 8cm hot-swap redundant PWM cooling fan(s)
7. 2 x 8cm hot-swap exhaust fan(s) & air shroud

Chassis Manual

Related products

Supermicro SuperChassis CSE-836BE1C-R1K03J ...
SuperChassis 836BE1C-R1K03J



Supermicro CSE-836BE2C-R1K28B
SuperChassis 836BE2C-R1K28B

Supermicro CSE-837E26-R1KB01
SuperChassis 837E26-R1KB01



SUPERMICRO 3U JBOD chassis 16x 3.5" HS SAS ...
SUPERMICRO 3U JBOD chassis 16x 3.5" HS SAS 12Gb/s

Supermicro CSE-836E1-R500B
SuperChassis 836E1-R500B

Supermicro CSE-833TQC-653B
SuperChassis 833TQC-653B

Supermicro CSE-833T-653B
SuperChassis 833T-653B

Add to cart