

 devnewton / gb3

Watch

1

Star

0

Fork

1

[Code](#) [Issues](#) [Pull requests](#) [Activity](#)

A KISS tribune powered by Go.

🕒 291 commits

⬆ 1 branch

🏷 64 tags

💽 525 KiB

📄 master ▾



Find a file

HTTPS

<https://codeberg.org/devnewtc>

...

 davenewton	bb28ca2db6	release 0.68	3 months ago
📁 cmd	fix sqlite for my good old debian		7 months ago
📁 deployments/kubernetes	use X-Accel-Buffering to disable proxy buffering		3 years ago
📁 docs	schema		3 years ago
📁 gc2	disable autocomplete on input aka firefox pete les couilles		4 months ago
📄 .dockerignore	kubernetes deployment		3 years ago
📄 .gitignore	prod ready cachetotoz		last year
📄 build-frugal.sh	one base, one sqlite, juste one solution		7 months ago
📄 build-with-full-features.sh	use pure go sqlite		7 months ago
📄 docker-compose.yml	gb2c: Make it possible to build SQLite support without CGO		7 months ago
📄 gb0.Dockerfile	Docker: Create volumes instead of relying on temporary direct...		7 months ago
📄 gb2c.Dockerfile	one base, one sqlite, juste one solution		7 months ago
📄 go.mod	fix sqlite for my good old debian		7 months ago
📄 go.sum	fix sqlite for my good old debian		7 months ago
📄 LICENSE	Initial commit		6 years ago
📄 nginx.conf	docker files		4 years ago
📄 README.md	one base, one sqlite, juste one solution		7 months ago
📄 release.sh	release 0.68		3 months ago

[README.md](#)

gb3

gb3 is a KISS cloud native tribune stack powered by [Go](#)

gb0

gb0 is a guiless bouchot.

Configuration

gb0 use the following environment variables.

GB0_LISTEN

Change default http listen address and port.

GB0_STORE_DIRECTORY

Post will be stored permanently to disk if this variable is a valid path to a writable directory.

If not set, a temporary folder will be used.

GB0_MAX_POSTS_IN_HISTORY

Maximum number of posts returned in TSV backend.

GB0_MAX_DAYS_IN_HISTORY

Maximum number of days in the past to consider for building TSV backend.

Endpoints

gb0 exposes two endpoint to retrieve and post messages.

/gb0/tsv

```
curl 'http://localhost:16667/gb0/tsv'
```

/gb0/post

```
curl -X POST -A "dave" -d "message=plop" 'http://localhost:16667/gb0/post'
```

or

```
curl -X POST -d "info=dave" -d "message=plop" 'http://localhost:16667/gb0/post'
```

gb2c

gb2c is a webservice providing API for coincoins.

Configuration

gb2c use the following environment variables.

GB2C_LISTEN

Change default http listen address and port.

GB2C_VERBOSE

Set to true to enable full logging.

GB2C_LINUXFR_CLIENT_ID and GB2C_LINUXFR_CLIENT_SECRET

Oauth credentials for linuxfr API.

GB2C_GB0_TRIBUNES

List of gb0 tribunes url. Default value is:

GB2C_GB0_TRIBUNES=devnewton:https://gb3.devnewton.fr,gabuzomeu:https://gb3.plop.cc

GB2C_MIAOLI_TRIBUNES

List of miaoli tribunes url. Default value is:

GB2C_MIAOLI_TRIBUNES=reveildutroll:https://miaoli.im/%2B6VtcdSCI0Y

GB2C_MAX_POSTS_IN_HISTORY

Maximum number of posts returned by poll requests. Default value is 200.

GB2C_STORE

The type of store to use: "sqlite" or "memory". Defaults to "memory".

GB2C_SQLITE_PATH

The path to the SQLite database where history can be saved

If not set, a temporary file will be used.

GB2C_SQLITE_MAX_POSTS_IN_STORAGE

The number of posts to keep in storage, 0 for unlimited. Default value is the current value of GB2C_MAX_POSTS_IN_HISTORY.

Endpoints

gb2c exposes exports for listing tribunes then polling and posting messages.

/gb2c/list

```
curl 'http://localhost:16666/gb2c/list'
```

/gb2c/poll

```
var postSource = new EventSource("http://localhost:16666/gb2c/poll");
postSource.onmessage = function (event) {
  console.log(event.data);
};
```

/gb2c/post

```
curl -X POST -d "info=dave" -d "message=plop" -d "tribune=euromussels" 'http://localhost:16666/gb2c/post'
```

gc2

A simple coincoin frontend for gb2c.

cachetotoz

A simple utility to cache [totoz](#) image and tags.

Configuration

cachetotoz use the following environment variables.

CACHETOTOZ_CACHE_DIRECTORY

Totoz images and tags will be stored permanently to disk if this variable is a valid path to a writable directory.

If not set, a temporary folder will be used.

Powered by

with modifications

Codeberg

[Blog](#)

[Documentation](#)

[Community Issues](#)

[Contributing](#)

[Report Abuse](#)

Association

[Who are we?](#)

[Bylaws / Satzung](#)

[Donate](#)

[Join / Support](#)

[Contact](#)

Services

[Codeberg Pages](#)

[Codeberg Translate](#)

[Woodpecker CI](#)

[Forgejo API](#)

[Status Page](#)

Legal

[Imprint / Impressum](#)

[Privacy Policy](#)

[Licenses](#)

